

C-Bus Micro Hub

CL-PK-MHA/CL-PK-MHB/CL-PK-10MHB-R

Version: 1.0.5



CL-PK-10MHB-R



CL-PK-MHB-R

C-Bus Micro Hub

The C-Bus Micro Hub is a compact module that functions as a hub for connecting Climax modules and provides neat solutions for installers in projects with several C-Bus supported modules.

The Climax products may connect to C-Bus Micro Hub via eight 5 mm screw terminals or RJ45 jacks.

By using a C-Bus Micro Hub, you can be more confident about designing, installing, troubleshooting and maintaining a reliable and easy-to-configure C-Bus network for your smart home.

- ✓ Compatible with smarthome systems
- ✓ Easier troubleshooting
- ✓ Neater wiring job
- ✓ Lower voltage drop
- ✓ Easy to mount either on rail or any other surface



CL-PK-MHA-R

C-Bus Micro Hub

CL-PK-MHA/CL-PK-MHB/CL-PK-10MHB-R

Product Specification

Version: 1.0.5

Technical Specification		
Part No.	C-Bus Connections	
	Number of RJ45 jacks	Number of rising-cages 5mm screw terminals sets (each contains 4 terminals)
CL-PK-MHA-R	2	4
CL-PK-MHA-S	2	4
CL-PK-MHB-R	4	2
CL-PK-MHB-S	4	2
CL-PK-10MHB-R	6	4
Dimensions		
Net (CL-PK-MHA-R, CL-PK-MHB-R)	Length	51.0 mm
	Width	44.0 mm
	Height	29.6 mm
Net (CL-PK-MHA-S, FI-PK-MHB-S)	Length	51.0 mm
	Width	67.8 mm
	Height	25.4 mm
Net (CL-PK-10MHB-R)	Length	71.9 mm
	Width	59 mm
	Height	28.4 mm
Packaged	Length	134.0 mm
	Width	107.0 mm
	Height	40.0 mm
Environmental		
Temperature	Operational	32° F - 95° F (0° C - 35° C) All load ratings are based on an ambient temperature of 25° C.
	Storage	14° F – 140° F (-10° C – 60° C)
Humidity	Operational	5% to 80% non-condensing
	Storage	5% to 95% non-condensing
Miscellaneous		
Housing		Poly(methyl methacrylate)
Color		Black
Mounting		
CL-PK-MHA-R, FI-PK-MHB-R, FI-PK-10MHB-R		Rail mounting
CL-PK-MHA-S, FI-PK-MHB-S		Screw mounting
Weight		
Part No.	CL-PK-MHA, CL-PK-MHB	CL-PK-10MHB-R
Net	45±5 gr	80±5 gr
Packaged	125±5 gr	160±5 gr