

GSM Modem

CL-DR-GSM

Version: 1.0.5



- ✓ Compatible with Control4 smart home systems
- ✓ Programmable based on calls and text messages
- ✓ Easy to mount either on rail or any other surface
- ✓ Power injected over C-Bus network
- ✓ Standalone functionality

GSM Modem

Climax GSM Modem delivers an effortless experience of remote access to smart home system. Alongside Control4 internet-based solutions, the ability to control smart home system via cellphone that is offered by this product enables users to have a generic solution to remotely manage their home automation system.

This reliable module provides the possibility of managing your smart home system through calling and sending text messages to the system from all over the world. It can turn on the TV, play a music, run a lighting scenario, open the garage door or any other action that has been set in home automation system.

Moreover, by reporting and sending feedbacks, it provides a 2-way communication between home automation system and user.

GSM Modem is equipped with integrated relay and input for digital sensors as well as detachable antenna and audio input and output. These gears ensure standalone functionality of this highly customizable module. GSM Modem can operate either in network mode through C-bus connections via "RS-232 GatewayPro" or in direct mode through direct connection with Control4 Home Controller.

GSM Modem

CL-DR-GSM

Product Specification

Version: 1.0.5

Technical Specification		
<i>Input Voltage</i>	<i>18V-24V DC (24V DC is recommended)</i>	
<i>Input Current</i>	<i>100mA (for 24V DC)</i>	
<i>I/O Connections</i>	<i>C-Bus</i>	<i>2 X RJ45</i>
	<i>RS232 (Direct Mode)</i>	<i>1 X RJ45</i>
	<i>Input</i>	<i>1 X digital dry contact input (rising-edge 5mm screw terminals)</i>
		<i>Audio input</i>
	<i>Output</i>	<i>1 X relay channel-8A per channel (rising-edge 5mm screw terminals)</i>
<i>Audio output</i>		
<i>Antenna Type</i>	<i>1 X 4dBi detachable omni-directional (RP-SMA)</i>	
DIMENSIONS		
<i>Net</i>	<i>Length</i>	<i>114.0 mm</i>
	<i>Width</i>	<i>90.0 mm</i>
	<i>Height</i>	<i>40.1 mm</i>
<i>Package</i>	<i>Length</i>	<i>162.0 mm</i>
	<i>Width</i>	<i>101.8 mm</i>
	<i>Height</i>	<i>81.4 mm</i>
Environmental		
<i>Temperature</i>	<i>Operational</i>	<i>32° F - 95° F (0° C - 35° C)</i> <i>All load ratings are based on an ambient temperature of 25° C.</i>
	<i>Storage</i>	<i>14° F – 140° F (-10° C –60° C)</i>
<i>Humidity</i>	<i>Operational</i>	<i>5% to 80% non-condensing</i>
	<i>Storage</i>	<i>5% to 95% non-condensing</i>
Miscellaneous		
<i>Housing</i>	<i>Acrylonitrile butadiene styrene (ABS)</i>	
<i>Color</i>	<i>Light almond</i>	
Weight		
<i>Net</i>	<i>170±5 gr</i>	
<i>Package</i>	<i>270±5 gr</i>	