

## IP GatewayPro

CL-DR-IPGWP-4X8A

Version: 1.0.1



### IP GatewayPro

The Climax IP GatewayPro is the basis of Climax smart home system and seamlessly integrates Climax modules into Control4 home automation system.

The IP GatewayPro communicates through the network and doesn't occupy any serial port from Control4 Home Controller.

IP GatewayPro is the right alternative to the RS-232 GatewayPro in large-scale projects with many Climax modules in longer distances.

- ✓ Compatible with Control4 home automation system
- ✓ Standalone functionality
- ✓ Mediator device between Control4 Home Controller and Climax modules
- ✓ Equipped with one extra serial port
- ✓ Equipped with one dry contact input sensor
- ✓ Doesn't occupy any serial port on Home Controller
- ✓ Easy to mount either on rail or any other surface

This affordable product is kitted up with 4 powerful relays to be utilized either in lighting or relaying functions of home automation projects. It is also equipped with one input channel which can be connected to any digital free voltage sensor or keypad.

# IP GatewayPro

CL-DR-IPGWP-4X8A

## Product Specification

Version: 1.0.1

<b>Technical Specification</b>		
Input Voltage	18V-24V DC (24V DC is recommended)	
Input Current	150mA (for 24V DC)	
I/O Connections	C-Bus	1 X RJ45
	RS-232	1 X RJ45
	Output	4 X relay channel-8A per channel (rising-cage 5mm screw terminals)
	Input	1 X digital dry contact input (pin1 & pin2 from RS-232 port)
	Network	2 X RJ45
<b>Dimensions</b>		
Net	Length	114.0 mm
	Width	90.0 mm
	Height	40.1 mm
Packaged	Length	162.0 mm
	Width	101.8 mm
	Height	81.4 mm
<b>Environmental</b>		
Temperature	Operational	32° F - 95° F (0° C - 35° C) All load ratings are based on an ambient temperature of 25° C.
	Storage	14° F - 140° F (-10° C - 60° C)
Humidity	Operational	5% to 80% non-condensing
	Storage	5% to 95% non-condensing
<b>Miscellaneous</b>		
Housing	Acrylonitrile butadiene styrene (ABS)	
Color	Light almond	
<b>Weight</b>		
Net	205±5 gr	
Packaged	305±5 gr	